

MANUAL COSSESS MANUAL SESSEES CONTRACTOR

NATIONAL BUREAU OF STANDARDS MICROCOPY RESOLUTION TEST CHART

ARL-TR-MAN

porture in the second s

Chief Tirel

APPLIED RESEARCH LASCARTORNE THE UNITED TO YEAR AND THE WAR TO YEAR THE THE PARTY SANCTION OF THE PARTY SANCTI

14 November 1985

Annuel Report: 1 July 1963 - 30 June 1984 Final Report: 1 July 1963 - 30 Repainter 1984


> Approved for public release; distribution unlimited.

> > Prepared for:

OFFICE OF NAVAL RESEARCH DEPARTMENT OF THE NAVY ARLINGTON, VA 22217







## UNCLASSIFIED

REPORT DOCUMENTATION PAGE	
	READ INSTRUCTIONS BEFORE COMPLETING FORM
The state of the s	3. RECIPIENT'S CATALOG NUMBER
AD-A163	
. TITLE (and Sublitio)	annual: 1 Jul 83 - 30 Jun 84
EXPERIMENTS ON SOUND PROPAGATION OVER SLOPED	final: 1 Jul 83 - 30 Sep 84
BOTTOMS	6. PERFORMING ORG. REPORT NUMBER
	ARL-TR-85-41
. AUTHOR(a)	8. CONTRACT OR GRANT NUMBER(+)
Halvor Hobaek	N00034 03 K 0503
Chris T. Tindle T. G. Muir	N00014-83-K-0593
PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT TASK
Applied Research Laboratories	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
The University of Texas at Austin	
Austin, Texas 78713-8029	<b>†</b>
11. controlling office name and address Office of Naval Research	12. REPORT DATE
Office of Naval Research Department of the Navy	14 November 1985
Arlington, VA 22217	13. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	18. SECURITY CLASS. (of this report)
·	1
	UNCLASSIFIED
	18a. DECLASSIFICATION/DOWNGRADING
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 26, If different fro	m Report)
port Control	
18. SUPPLEMENTARY NOTES	
	uide, <del>(</del>
shallow water acoustics;acoustic waveg modal propagation;	
Shallow water acoustics, acoustic waveg modal propagation sound propagation  Shallow water acoustics, acoustic waveg modal propagation  Shallow water acoustics, acoustic waveg modal propagation  Shallow water acoustics, acoustic waveg modal propagation acoustic waveg modal propagation  Shallow water acoustics, acoustic waveg modal propagation acoustic waveg waveg modal propagation acoustic waveg modal propagation acoustic waveg waveg modal propagation acoustic waveg waveg waveg waveg waveg	
shallow water acoustics; acoustic waveg modal propagation; sound propagation  S. KEY WORDS (Continue on reverse elde if necessary and identify by block number,	w water wedge have been were on of adiabatic normal ly to the local water. For upslope propagation, epth is directed into the or downslope propagation, wavefronts and not with

UNCLASSIFIED CURITY CLASSIFICATION OF THIS PAGE(When Date Entered	use single
	# 4
20 (Cont'd)	h h
In addition, normal modes not present the water depth is sufficient to suppo	at the source can be "captured" when out them. Keywords: (top 1)
•	magnitude (1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1
•	


UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered,

### TABLE OF CONTENTS

		<u>Page</u>
LIST	OF FIGURES	v
I.	INTRODUCTION	1
II.	EXPERIMENTAL ARRANGEMENT	3
III.	ANALOG RESULTS	5
IV.	WAVEFORM RESULTS	9
٧.	SUMMARY AND CONCLUSIONS	15
ACKNO	OWLEDGMENT	17
REFER	RENCES	19

AND AND PROPERTY OF THE PARTY O



### LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Analog Records at a Range of 7.4 m for Propagation Downslope at $1^{0}$	6
2	Analog Records for Propagation Upslope at 0.60	. 7
3	Normal Mode Waveforms at Bottom Slopes of (a) $0^{\circ}$ and (b) $1^{\circ}$ at a Range of 7 m. Using a Single Source at Midwater Depth	10
4	Hydrophone Waveforms and Normal Mode Waveforms at a Range of 4.5 m and a Slope of 90	12
5	Normal Mode Waveforms at Bottom Slopes of (a) $1^{\circ}$ and (b) $3^{\circ}$ at Range of 4 m	13

#### I. INTRODUCTION

Issues raised by recent theories of propagation into and out of a shallow water ocean wedge require precise and comprehensive measurements of the sound field in the water and the bottom for a variety of ranges and bottom slopes. These measurements are difficult in the ocean, and so we have performed a scaled model experiment in an indoor tank. Typical operating parameters are a water depth at the source of five wavelengths, ranges up to 500 wavelengths, and slopes up to  $9^0$ .

The objective of the experiment was to study propagation of normal modes in a smooth plane wedge. Early experimental work by Eby et al. and theoretical work by Pierce and Milder suggested that normal modes far from cutoff behave adiabatically and adjust to the local water depth.

Recent numerical calculations by Jensen and Kuperman<sup>4</sup> suggested that as a normal mode passes upslope through its cutoff depth, its energy is transferred to the bottom with negligible coupling to lower modes.

Our results for a wider range of slopes and a greater number of modes are in agreement with the earlier work. A selection of our results is presented here and two new effects associated with propagation on slopes are described.

#### II. EXPERIMENTAL ARRANGEMENT

The ocean bottom in the model experiment is formed by a tray of sand  $10 \text{ m} \log x 1 \text{ m}$  wide x 20 cm deep. The sides and bottom of the tray are lined with random scatterers to eliminate specular reflections. The tray is suspended in the water and the slope and depth of the bottom can easily be varied. The sand has a sound speed of 1787 m/s, a density of 1.97 g/cc, and an attenuation of about 0.8 dB/wavelength.

all appresses property property. Browner replaces

The experiment was designed to use a line source operating in 10 cm of water at 80 kHz. There are six normal modes present in this case and the line source of seven elements can be shaded in phase and amplitude to generate individual normal modes. In reality, there is always some slight contamination from other modes but this does not lead to any difficulties in interpreting the results.

In some cases it is convenient to use a single point source rather than a line source; this is easily achieved by exciting an individual element of the source array.

The acoustic signals are received by a small probe hydrophone which can be positioned at any given range and then moved accurately in a vertical direction. The vertical movement is connected via a servo-mechanism to an analog chart recorder.

Data can be taken by two complementary methods. Analog chart recordings of signal level (in dB) as a function of depth can be obtained by simply operating the vertical movement of the probe hydrophone. In this method we use a gating technique described by Eby et al. An electronic gate is set to detect the peak value of the signal within a small time interval. The time interval is chosen to coincide with the arrival of the mode under investigation, thus enabling the contamination from other modes to be minimized.

The second method of taking data is to fix the range and depth of the probe hydrophone and to digitize the entire waveform of the received signal. It is a simple matter to take recordings at various depths. These can be treated as if they were simultaneous recordings on a vertical array of hydrophones because the start of the digitization interval is accurately controlled.

It is well known<sup>5</sup> that signals from a vertical hydrophone array can be combined in a suitably weighted summation to allow extraction of the waveforms present in each individual normal mode. In the following figures the normal mode waveforms were obtained using this technique.

THE TOTAL PROPERTY OF THE PROP

#### III. ANALOG RESULTS

THE PROPERTY OF THE PARTY OF TH

Analog results of signal level as a function of depth have been taken for a variety of cases. Figure 1 shows results for downslope propagation at 1° of bottom slope. The line source was shaded to generate modes 1, 2, and 3 successively, and the resulting analog traces are shown. It is clear that the modes have adjusted adiabatically to the local water depth of 22.9 cm. The small variation in the amplitude of modes 2 and 3 for different maxima of the same mode is consistent with contamination by other modes due to imperfect shading of the line source. It is not thought to be associated with coupling of energy between modes. The small oscillations in the bottom, some 35 dB below the maximum signal level in the water, represent the noise level of our measurements and are possibly due to sound propagating down the hydrophone support.

Figure 2 shows results for propagation upslope at 0.6°. The line source in 10 cm water depth was shaded to preferentially excite mode 2. Figure 2(a) shows that mode 2 has adjusted to the local water depth of 4.8 cm. The field in the bottom falls off very rapidly. In Fig. 2(b) the water depth has decreased to 2.7 cm, and the "tail" of the mode falls off much more slowly in the bottom. In Fig. 2(c) the water depth is 2.4 cm, and mode 2 has passed beyond cutoff. There is now a substantial amount of energy propagating in the bottom. In Fig. 2(d) mode 2 has disappeared from the water column, and the field in the water is due to the small amount of mode 1 generated by the line source. The remaining energy of mode 2 is now propagating as a broad, strongly attenuated beam of sound whose axis has moved deeper into the bottom; this result is consistent with the numerical calculations of Jensen and Kuperman. The results shown in Fig. 2 should be regarded as preliminary, as the origin of the small oscillations in the bottom is uncertain.




FIGURE 1

ANALOG RECORDS AT A RANGE OF 7.4 m FOR PROPAGATION DOWNSLOPE AT 1°

THE LINE SOURCE IN 10 cm WATER DEPTH WAS SHADED TO MODES 1, 2, AND 3 SUCCESSIVELY

THE RECORDS SHOW THAT THE MODES HAVE ADJUSTED ADIABATICALLY TO THE LOCAL

WATER DEPTH OF 22.9 cm




FIGURE 2

ANALOG RECORDS FOR PROPAGATION UPSLOPE AT 0.6°

THE LINE SOURCE WAS SHADED FOR MODE 2

RANGES ARE (a) WELL BEFORE CUTOFF, (b) JUST BEFORE CUTOFF,

(c) BEYOND CUTOFF, AND (d) WELL BEYOND CUTOFF

THE DASHED CURVE IN (d) INDICATES THE SEPARATELY MEASURED LEVEL OF MODE 1

WATER DEPTH AT EACH RANGE IS INDICATED ON THE FIGURES

#### IV. WAVEFORM RESULTS

In constant water depth each individual normal mode travels with its own group velocity. Thus, if a point source emits a short pulse, the signal received downrange will be a series of possibly overlapping pulses associated with each mode. The individual normal mode waveforms can be extracted, an example of which is shown in Fig. 3(a). A point source at midwater depth was excited using a smoothly rising and falling pulse of approximately four cycles. The source element "rings" after the excitation is removed, so the decay of the pulse in the water is slower than its rise time. The waveform of mode 1 in Fig. 3(a) is very similar to that of the pulse emitted by the source.

The other mode waveforms in Fig. 3(a) show the well known features of normal mode propagation in isovelocity layers. In particular, (1) higher modes arrive progressively later due to their lower group velocities, (2) the pulses of higher modes are more dispersed due to their greater variation of group velocity with frequency, and (3) higher modes suffer progressively greater attenuation.

When the bottom is sloping, the above features are still present but the extent of each feature is strongly affected by even a small slope, as can be seen by comparing Figs. 3(a) and 3(b). Figure 3(b) shows the waveform obtained at the same range as Fig. 3(a) for downslope prepagation at  $1^0$  of bottom slope. The relative arrival times of the higher modes are now much reduced. For example, the time interval between the peaks of modes 1 and 4 is reduced from 0.25 ms to 0.11 ms. The dispersion in the higher modes is also much reduced.

Another important effect of the slope is the severely reduced attenuation of the higher modes. Mode 6 is easily observed at  $1^0$  of bottom slope and yet for constant water depth, mode 6 is barely present at this range and could not be detected at greater ranges.




FIGURE 3

NORMAL MODE WAVEFORMS AT BOTTOM SLOPES OF (a) 0° AND (b) 1°

AT A RANGE OF 7 m USING A SINGLE SOURCE AT MIDWATER DEPTH

WATER DEPTH AT THE SOURCE IS 10 cm AND PROPAGATION IS DOWNSLOPE

THE SMALL SECOND ARRIVALS PRESENT IN MODE 1 (AND VERY SLIGHTLY
IN MODE 2) ARE REFLECTIONS FROM THE TANK WALL AND SHOULD BE IGNORED

The above features of downslope propagation are all consistent with simple adiabatic normal mode theory. As the water depth increases, the group velocity should decrease, the dispersion should be reduced, and the attenuation should be reduced as the "exponential tail" of the mode penetrating into the bottom decreases.

We have taken data at bottom slopes of up to  $9^{\circ}$ , and the above effects continue to be observed. Figure 4(c) shows normal mode waveforms at  $9^{\circ}$ . The source waveform used was a very sharply defined four-cycle pulse, very similar to that shown for mode 1, which propagates with negligible dispersion. The time separation between successive modes is seen to be very small for large bottom slopes.

The mode waveforms of Fig. 4(c) were obtained from the hydrophone data of Fig. 4(a). The first part of the waveforms of Fig. 4(a) are shown on an expanded item scale in Fig. 4(b) to illustrate the time delay which occurs for the deeper hydrophones due to the sloping bottom. The time delay between top and bottom hydrophone waveforms for Figs. 4(a) and (b) is 0.035 ms and corresponds to 2.8 wavelengths.

TOTAL CONTROL STREET TOTAL CONTROL CON

The first arrival of the signals has a delay which is consistent with spherical spreading from the point source. In performing the extraction of the mode waveforms, it was necessary to shift the hydrophone waveforms in time to synchronize them. The fact that the extraction of the mode waveforms is then successful shows that the normal modes do not propagate as wavefronts which are simultaneous at all depths. Instead, they propagate as spherical wavefronts. This is in contrast to simple adiabatic normal mode theory which assumes that normal modes propagate as vertical wavefronts.

An interesting new effect is illustrated in Fig. 5, which shows mode waveforms at a range of 4 m and slopes of  $1^{\circ}$  and  $3^{\circ}$ . The source is placed near the surface in only 5 cm of water. This water depth can support only three normal modes but we see in Fig. 5(b) that four normal modes are present in the received signal. It is clear that energy





FIGURE 4

HYDROPHONE WAVEFORMS AND NORMAL MODE WAVEFORMS
AT A RANGE OF 4.5 m AND A SLOPE OF 9°

WATER DEPTH AT THE SOURCE IS 10 cm WITH THE SOURCE AT MIDWATER DEPTH
AND PROPAGATION IS DOWNSLOPE

(a) WAVEFORMS AT SUCCESSIVE DEPTHS AS INDICATED, (b) SAME AS (a) BUT WITH
EXPANDED TIME SCALE TO SHOW THE DELAY BETWEEN SIGNALS ARRIVING AT THE
TOP AND SUCCESSIVELY LOWER HYDROPHONES,

(c) MODE WAVEFORMS EXTRACTED FROM THE HYDROPHONE WAVEFORMS OF (a)



SOUR CARRY GRANDS SECURE AND DESCRIPTION OF THE PROPERTY OF TH

FIGURE 5

NORMAL MODE WAVEFORMS AT BOTTOM SLOPES OF (a) 1° AND (b) 3° AT RANGE OF 4 m

THE SOURCE IS NEAR THE SURFACE IN 5 cm OF WATER AND PROPAGATION IS DOWNSLOPE

coupling into mode 4 is not present at the source as a discrete mode. Therefore, some of the energy which is usually associated with the continuum can be trapped when the water depth is sufficient to support another discrete mode. Thus a normal mode which is not present at the source can become "captured" as the water depth increases. This effect had been noted earlier in the theoretical calculations of Tindle and Deane. 6

occel cossess members seemed veryout members

#### V. SUMMARY AND CONCLUSIONS

- 1. The experiment has confirmed the assumption of adiabatic normal mode theory that, for a smooth plane wedge, the mode shape adjusts continuously to the local water depth. The group velocities of the modes are also consistent with the adiabatic assumption.
- 2. The experiment has shown that, as a mode passes through cutoff in upslope propagation, its energy enters the bottom as a beam, and that there is negligible coupling to lower modes.
- 3. Mode coupling effects, if they exist, are very small.

SEL PERSONAL PROCESSES CARRESTED EXPERSON PROCESSES SERVICES ANALOGICAL PROCESSES FOR PROCESSES OF THE PERSONS OF THE PERSONS

- 4. The normal modes propagate downslope as curved wavefronts, and not as the vertical wavefronts of simple adiabatic normal mode theory.
- 5. Modes not trapped in the water depth at the source may be "captured" when the water depth increases.

#### **ACKNOWLEDGMENT**

H. Hobaek is grateful for partial support from the Norwegian Council for Science and the Humanities.

ENTER PROPERTY SERVICES CONTROL OF THE PROPERTY OF THE PROPERT

#### REFERENCES

- R. K. Eby, A. O. Williams, Jr., R. P. Ryan, and Paul Tamarkin, "Study of Acoustic Propagation in a Two-Layered Model", J. Acoust. Soc. Am. 32, 88-99 (1960).
- A. D. Pierce, "Extension of the Method of Normal Modes to Sound Propagation in an Almost-Stratified Medium", J. Acoust. Soc. Am. 37, 19-27 (1965).
- D. M. Milder, "Ray and Wave Invariants for SOFAR Channel Propagation", J. Acoust. Soc. Am. <u>46</u>, 1259-1263 (1969).
- 4. F. B. Jensen and W. A. Kuperman, "Sound Propagation in a Wedge Shaped Ocean with a Penetrable Bottom", J. Acoust. Soc. Am. 67, 1564-1566 (1980).
- 5. C. T. Tindle, K. M. Guthrie, G. E. J. Bold, M. D. Johns, D. Jones, K. O. Dixon, and T. G. Birdsall, "Measurements of the Frequency Dependence of Normal Modes", J. Acoust. Soc. Am. <u>64</u>, 1178-1185 (1978).
- 6. C. T. Tindle and G. B. Deane, "Sound Propagation over a Sloping Bottom Using Rays with Beam Displacement", J. Acoust. Soc. Am. (accepted for publication).

。 1960年1日,1960年1962年,1960年1962年,1960年1962年,1960年1962年,1960年1962年,1960年1962年,1960年1962年,1960年1962年,1960年1962年,196

## ARL-TR-85-41 ANNUAL REPORT AND FINAL REPORT UNDER CONTRACT NOO014-83-K-0593

	Control of the Contro
	1.4 No.
	14 Nov
	0.070.10.11.11.1.10.1.10.1.10.1.10.1.10
	DISTRIBUTION LIST FOR  ARL-TR-85-41
Δ	NNUAL REPORT AND FINAL REPORT UNDER CONTRACT NOO014-83-K-C
•	
Copy N	<u>).</u>
	Chief of Naval Research
	Department of the Navy
	Arlington, VA 22217
1	Attn: R. Fitzgerald (Code 425VA)
2	R. Obrochta (Code 425AR)
	Commanding Officer
	Naval Sea Systems Command
	Department of the Navy
	Washington, D.C. 20362
3	Attn: D. Porter (PMS 407)
	Commanding Officer
	Space and Naval Warfare Systems Command
	Department of the Navy
	Washington, D.C. 20363-5100
4	Attn: J. Schuster (Code 612)
5 6	R. Mitnick (Čode PM124)
6	K. Hawker (Code PM124)
	Commanding Officer
	Naval Air Systems Command
	Department of the Navy
	Washington, D. C. 20362
7	Attn: W. Emschweiler (Code 548)
	Defense Advance Research Projects Agency
	1400 Wilson Blvd.
	Arlington, VA 22209
8	Attn: C. Stuart
	Commanding Officer
	Office of Naval Technology
	Department of the Navy
	Arlington, VA 22217
9	Attn: W. Ching (Code 0715)
	,
	Commanding Officer
	Mine Warfare Command
	Naval Base
	Charleston, SC 29408 Attn: G. Pollitt

Distribution List for ARL-TR-85-41 under Cont. NOO014-83-K-0593 (cont'd)

#### Copy No.

11 12 13 14	Commanding Officer Naval Research Laboratory Washington, D.C. 20375 Attn: W. Kuperman (Code 5160) S. Wolf F. Ignenito Librarian
15 16 17	Commanding Officer Naval Ocean Systems Center Department of the Navy San Diego, CA 92152 Attn: H. Bucker (Code 30) G. Pennoyer Librarian
18	Commanding Officer Naval Undersea Systems Center Department of the Navy San Diego, CA 92132 Attn: Librarian
19 20 21	Director Naval Postgraduate School Monterey, CA 93940 Attn: H. Medwin A. Coppens Librarian
22 - 33	Commanding Officer Defense Technical Information Center Cameron Station, Bldg. 5 5010 Duke Street Alexandria, VA 22314
34 35	Director Applied Research Laboratory The Pennsylania State University P. O. Box 30 State College, PA 16801 Attn: S. McDaniel Librarian

Distribution List for ARL-TR-85-41 under Cont. N00014-83-K-0593 (cont'd)

#### Copy No.

である。 「一般のでは、「一般のできない。」というないできない。 「一般のできない。」というないできない。 「一般のできない。」 「一般のできない。 「一をない。 「一をない。 「一をない。 「一をない。 「一をない。 「一をない。 「一をない。 「一を

36 37	Director Marine Physics Laboratory Scripps Institution of Oceanography University of California San Diego, CA 92152 Attn: F. Fisher Librarian
38 39	Applied Physics Laboratory University of Washington 1013 NE 40th Street Seattle, WA 98105 Attn: D. Jackson Librarian
40	Case Western Reserve University University Circle Cleveland, Ohio 44106 Attn: L. Felsen
41	Industrial Acoustics Laboratory Institute of Manufacturing Engineering Technical University of Denmark, Bldg. 352 DK-2800 Lyngby DENMARK Attn: L. Bjørnø
42	Department of Physics Bergen University N-5014 Bergen NORWAY Attn: H. Hobaek
-	
43	T. G. Muir, ARL:UT
44	Clark S. Penrod, ARL:UT
45	Chris T. Tindle, ARL:UT
46	Library, ARL:UT
47 - 56	Reserve, ARL:UT

# END

FILMED

2-86

DTIC